

DVP-SR110/SR120/SR320

RMT-D197A/D197P

SERVICE MANUAL

Ver. 1.2 2011.06



Photo: DVP-SR110

Australian Model
Mexican Model
DVP-SR110
E Model
Russian Model
Singapore Model
Thailand Model
Kuwait Model
UAE Model
DVP-SR120/SR320
Brazilian Model
India Model
Middle East Model
South Africa Model
DVP-SR320

SPECIFICATIONS

System

Laser: Semiconductor laser

Outputs

LINE OUT L/R (AUDIO): Phono jack

DIGITAL OUT (COAXIAL): Phono jack

LINE OUT (VIDEO): Phono jack

USB (DVP-SR320 only): USB jack Type A,
maximum current 500mA (For connecting
USB device)

General

Power requirements:

110-240V AC, 50/60Hz (except MX/RUS)

120V AC, 60Hz (MX)

220-240V AC, 50/60Hz (RUS)

Power consumption: 6W (DVP-SR110/SR120)
10W (DVP-SR320)

Dimensions (approx.): 270×38.5×209mm

(width/height/depth) incl. projecting parts

Mass (approx.): 950g

Operating temperature: 5°C to 35°C

Operating humidity: 25 % to 80 %

Supplied accessories

- Audio/Video cord (phono plug × 3 ↔ phono plug × 3) (1)
- Remote commander (remote) (1)
- R6(Size AA) batteries (2)

Specifications and design are subject to change
without notice.



CD/DVD PLAYER

SONY®

REPAIR PARTS LIST

1 Remote Commander



Photo: RMT-D197A

Ref. No.	Part No.	Description	Remark	• Abbreviation
1	1-489-429-11	REMOTE COMMANDER (RMT-D197P)	(Except E/MX)	E : Latin America model
1	1-489-430-11	REMOTE COMMANDER (RMT-D197A)	(E/MX)	MX : Mexican model

REVISION HISTORY

[illegible]